

DWR50 COLOUR

PERFORMANCE CHARACTERISTICS

- Provides vivid colour prints with good coverage
- Good scratch and smudge resistance
- Excellent print quality on a wide variety of substrates
- Prints at speeds up to 6 inches per second delivering deep, crisp images
- Compatible with all flat head thermal transfer printers
- Available in over 17 different colours
- Availability in single rolls in 110mm x 150m
- Heavy metal free, meets EN71



RIBBON SPECIFICATIONS	
DESCRIPTION	TECHNICAL
BASE FILM CARRIER	4.5 Micron Polyester
TOTAL RIBBON THICKNESS	7.0 Microns
INK TYPE	Wax/Resin (flat head technology)
COLOUR	Various
INK MELTING POINT	72°C
DENSITY	Varies according to colour

RIBBON STORAGE CONDITIONS	
DESCRIPTION	TECHNICAL
TEMPERATURE	5°C to 35°C (41F to 95F)
HUMIDITY	10% to 85% relative humidity
LIGHT	Avoid direct sunlight

CERTIFICATIONS AND APPROVALS:	
DESCRIPTION	TECHNICAL
ISO 9001:2000 & ISO 14001:2004 BRC-Global standards for packaging RoHs/WEEE	All ribbons have been manufactured to these international quality standard EC directives 2002/65 and 2002/96, compliance to the limitation of dangerous substances in electrical and electronics equipments
HEAVY METALS TSCA/CP 65 AMES TEST EC DIRECTIVES	EC 98/638 The ribbon does not contain any of the substances on this list The ribbon is not mutagenic, does not cause DNA modifications 1999/45/EC and 2001/59/EC. This ribbon does not contain any substance classified as dangerous for health
DISPOSAL	To be disposed of as mixed industrial waste

This information is the best available on the above ribbon grade. These results should, however, only be regarded as a general guide to material properties and is not a guarantee.



Datamark UK Limited, Unit 3b, Banner Court, Henry Boot Way,
Priory Park East, Hull, East Yorkshire, HU4 7DX
t: 01482 506560 / 505101 | f: 01482 504758
e: sales@datamarkuk.com | www.datamarkuk.com

