

# DMR20

## PRODUCT DESCRIPTION


This resin grade is the recommended ribbon where durability of the printed image is required. It offers excellent scratch resistance, and is noted for its adaptability and excellent print performance over a wide variety of media.

It has been engineered to give maximum performance over a wide range of energy settings, making for easy change with other resin products with little or no printer adjustment required. This resin offers the blackest of prints and maximum scratch resistance, with possible print speed up to 300mm/sec.


A premium backcoat technology ensures maximum printhead protection extends print head life. This grade can be confidently specified with a wide range of proprietary label brands and on all types of flat head technology printers.

## RECOMMENDED SUBSTRATES

Coated and synthetic papers, polyethylene, polypropylene, polyester, polyvinylchloride



## PERFORMANCE PROPERTIES



## EXAMPLES OF TYPICAL APPLICATIONS



AUTOMOTIVE



OUTDOOR



HEALTHCARE



SHRINK WRAP



GENERAL



GENERAL



ASSET  
TRACKING



ELECTRONIC  
COMPONENTS



CHEMICAL  
DRUM



SIGNAGE

# DMR20

## PERFORMANCE CHARACTERISTICS

- > Super Scratch resistance
- > Low printhead energy required
- > Ideal choice for general high durability labelling applications
- > Ideal for rating plates, automotive, outdoor, pharmaceutical labels
- > High speed printing up to 12" inches per second
- > ISEGA certification



RIBBON SPECIFICATIONS		RIBBON STORAGE CONDITIONS	
DESCRIPTION	TECHNICAL	DESCRIPTION	TECHNICAL
BASE FILM CARRIER	4.5 Micron Polyester	TEMPERATURE	5°C to 35°C (41F to 95F)
TOTAL RIBBON THICKNESS	6.7 Microns	HUMIDITY	10% to 85% relative humidity
INK TYPE	Resin (flat head technology)	LIGHT	Avoid direct sunlight
COLOUR	Black		
INK MELTING POINT	70-80°C		
DENSITY	>1.8		

CERTIFICATIONS AND APPROVALS	
DESCRIPTION	TECHNICAL
ISEGA	FDA
EU Food directive	Halogen Free
BRC	
RoHS	
REACH	

This information is the best available on the above ribbon grade. These results should, however, only be regarded as a general guide to material properties and is not a guarantee.



BS 5609



Datamark UK Limited, Unit 3b, Banner Court, Henry Boot Way,  
Priory Park East, Hull, East Yorkshire, HU4 7DX

t: 01482 506560 / 505101 | f: 01482 504758

e: sales@datamarkuk.com | [www.datamarkuk.com](http://www.datamarkuk.com)

